









For additional information relating to price levels and technical data, please contact sales@formiko.lv





Hydraulic rotator FHR 4.500SF is cost-effective solution generally for seasonal use in forestry, agriculture, general cargo and material handling.



Rotator's upper mount is applied in EYE form factor of the knuckle joint. Robust and tough built to withstand even overloads. The wide of eye is common standard width 73mm and the knuckle pin diameter 25mm.



Rotator lower mount is applied in SQUARE shape FLANGE form factor to mount dirrect on grapple / tool surface by fixing with screws



Rotator FHR 4.500SF based on reliable vane type hydraulic motor which delivers torque up to 1200Nm at 25MPa.



Some parts in rotator are built from shock resistant and deformation resistant forged steel.



Formoko rotator FHR 4.500SF is compatible with FHL 01-A/B-73/25 and FHL 01B-A/B-73/25 series links.



Rotator for shipping is packed in compact solid cardboard box with dimensions 340x230x240mm.



We providing TWO year warranty for this rotator.

For additional information relating to price levels and technical data, please contact sales@formiko.lv

Formiko Hydraulic s Ltd Dzirciema Str. 119 k-1, Riga LV1055 LATVIA

+371 2 94 49 552 +371 2 64 59 383 sales@formiko.lv www.formiko.lv On request by special conditions there are metric nipples available for rotator FHR 4.500SF



Current document is automatic generated at www.formiko.lv on 08/21/2018.

Please always make sure that it's up to date and try to be paperless!